

KIP 7770 Specifications

Compatible File Formats





Single Footprint KIP 7770 Print System

0 1 0 5 "		
System Configurations		
2 Roll Print System	B&W wide format printer	
4 Roll Print System	B&W wide format printer	
Stacking Systems (standard)	Integrated top stacking - up to 50 sheet capacity	
Stacking Systems (optional)	High capacity print tray, KIP 1200 stacker	
Multifunction Scanning Systems (optional)	KIP 720 CIS scanner	
Production Scanning Systems (optional)	KIP 2300 CCD scanner	
Folding Systems (optional)	KIPFold 1000, KIPFold 2000	
Media Capacity Upgrade (optional)	Additional 2 roll media drawer to increase capacity from 2 rolls to 4 rolls	
General		
Print Technology	Electrophotography (LED) with organic photoconductor (OPC) and closed toner system	
Speed	9 D / 5 A0 size pages per minute, FPOT (First Print Output Time) 18 seconds D / A1 size page	
Warm Up Time	Instant from standby, <4 minutes from start up	
Configurations	Printer or multifunction system (print/copy/scan) 2 or 4 rolls	
Roll Options	2 or 4 rolls - 11" - 36" / 297 mm - 914 mm roll width	
Electrical Requirements	220-240 V, 50/60 Hz, 16 A	
Power Consumption	Sleep: <14 W Printing: 2.0 kW	
Dimensions	67" (w) x 29" (d) x 59" (h) / 1702 mm (w) x 725 mm (d) x 1510 mm (h) with front delivery tray	
Weight	2 Roll: 734 lb. / 333 kg 4 Roll: 827 lb. / 375 kg	
Printer		
Print Resolution	600 x 2400 dpi	
Paper Capacity	3000/6000 sq. ft. / 297/558 sq. m, max 2/4 rolls	
Output Sizes Width	11" - 36" / 297 mm - 914 mm	
Output Sizes Length	Length: 20' / 6 m (standard), 79' / 24 m (optional)	
Paper Weight	Bond-Plain 18-24 lb. / 64-90 gsm, vellum-translucent-tracing 18-20 lb. / 80 gsm, film 3.5-4 mil / 75 micron	
Media Type	Bond-plain, vellum-translucent-tracing, film (compatible with recycled & colored bond)	
Controller		
Controller Type	KIP System K Controller with Windows 7 Embedded	

PDF, DWF, HPGL 1/2, HP-RTL, Calcomp 906/907, CALS Group 4, TIFF Group 4, PCX, CIT/TG4, Uncompressed, Grayscale TIFF, TIFF Packbits, PNG, JPEG



Single Footprint KIP 7770 Multifunction System

Optional KIP 720 Scanner	
Scanner Type	C.I.S. with KIP RTT Technology
Scan Resolution	600 x 600 dpi optical resolution
Scan Speed	Up to 8 ips / 203 mm per second (B&W) Up to 2.6 ips / 66 mm per second (Color)
Scan Format	TIFF, Multipage TIFF, PDF, PDF-A, Multipage PDF, DWF, Multipage DWF, JPEG, CALS
Scan Destination	Local USB (removable media), unlimited system mailboxes (local), unlimited FTP, unlimited SMB, unlimited cloud connect to OneDrive, Google Drive or Dropbox, Box.com, Microsoft SharePoint & Microsoft Office 365 Online™
Original Size Width	8.5" - 36" / 210 mm - 914 mm
Original Thickness	Up to 1.6 mm thick
Interface	USB 2.0
Dimensions	45" (w) x 14" (d) x 6.3" (h) / 1140 mm (w) x 360 mm (d) x 160 mm (h)
Weight	53 lbs. / 25 kg
Electrical	100-240 V AC 50/60 Hz
Power Consumption	<50 W







Dual Footprint KIP 7770 Production System

Optional KIP 2300 Scanner		
Scanner Type	C.C.D. with KIP Tru•Speed Technology and KIP RTT Technology	
Scan Resolution	600 x 600 dpi optical resolution	
Scan Speed	Up to 12 ips / 305 mm per second (B&W) Up to 6 ips / 152 mm per second (Color)	
Scan Formats	TIFF, Multipage TIFF, PDF, PDF-A, Multipage PDF, DWF, Multipage DWF, JPEG, CALS	
Scan Destination	Local USB (removable media), unlimited system mailboxes (local), unlimited FTP, unlimited SMB, unlimited cloud connect to OneDrive, Google Drive or Dropbox, Box.com, Microsoft SharePoint & Microsoft Office 365 Online™	
Original Size Width/Length	8.5" - 42" (36" scan area) / 210 mm - 1066 mm (914 mm scan area)	
Original Thickness	Up to 0.6" / 16 mm automatic thickness detection	
Original Face Up/Face Down	Both - dual original feed tables	
Interface	USB 2.0, KIP Tru•Speed Technology (2.3 GB per second data transfer)	
Dimensions	54" (w) x 21" (d) x 13" (h) / 1360 mm (w) x 540 mm (d) x 320 mm (h)	
Weight	160 lbs. / 73 kg	
Electrical	100-240 V AC 50/60 Hz	
Power Consumption	<120 W	



KIP Systems K Multi-Touch Screen		
KIP Multi-Touch Touchscreen	Swipe, Pinch, Spread and Rotate Print Directly from Rem	ng Angle Print, Copy and Scan in B&W and Full Color* Super View for ovable Media, the Cloud and Local Mailboxes Full Color User Guides Manage History Queue Optional KIP Color Plus for Copy and Print in
KIP Color Copy & Print Plus		onnection via IP Address Quick Closed Loop Calibration for Accurate or and B&W Functions Real Time Image Preview Full Screen Color Color Adjustments
KIP Cloud Connect		Connect Scan to KIP Cloud Connect Unlimited Cloud Connections and Services for Single Print Job Easy Configuration from Multi-Touch
(IP Systems K Print Drivers		
Windows® Driver		ime System Status Information Set Collation Provides Current Media lob on Hold Save Templates Brightness Adjustment Unlimited Image
AutoCAD Driver		HDI AutoCAD Driver 32 and 64 Bit Operating System Compatibility n Media Saving by Auto Rotation Advanced Color Mode Image Type
(IP Data Security Features		
KIP Data Security Features	Image Overwrite Removable Hard Disk Drive Accessory Standard Security Updates Data Encryption and Virus Sca	y Kit System K Operating System Windows® Embedded System 7 anning Applications KIP Secure Print
(IP Systems K Print Submission		
KIP PrintPro	Settings Color Adjustments and Filter Selections Email N	eview Individual File Settings for Job Matrix Templates Multi-Page Notification Customize Job Build Matrix Windows Document Folding 8 and Vista Compatible (32 and 64 Bit) Customize System and Folde
KIP PrintPro.net		Individual File Settings for Job Matrix Templates Multi-Page Support Coloent Folding and Stamping HPGL Pen Preset Selection Transfer Files from Manage Print Queue and User Settings KIP Secure Print
KIP GraphicPro	TIF Filter Editor for Color Control ICC Profile Support for	or Printing Job Editor for Mixed B&W and Color Sets Multi-Page PDF. CMYK and RGB Color Management Factory /Custom Media Profiles and Vertical Paneling Area of Interest (Zoom to Area and Print) B&W
KIP Smart Print & Scan		th any Web Enabled KIP Printer Print B&W or Color Documents Scar ote Scan Auto-Archived or Printed by KIP Printer Optional Keywords
(IP Systems K Accounting / Administra		
KIP Accounting Center		a Using LDAP Clear Fields After Each Job Submission ASCII Import Automated KIP System Update via Scripting Password Protect any o
KIP Cost Center	Graphical Reports Average Toner Coverage by Percent	Track Color and B&W Copy, Scan and Print Easy to Understand Daily Print and Scan Volume for Color and B&W User, Project and Dobs KIP Toner Costs by Color and B&W KIP Maintenance Costs
KIP Card Reader Systems	Certified Card Reader User Authentication Linked to Card SMB Credentials Track Usage by Card/NFC Token Relea Cost Center Integration Common Access Card Solution: E	Cards Various Contactless NFC Tokens and Cards NFC Forum - d/NFC Token Load User and System Presets Load User Cloud and ase User Jobs at Touchscreen KIP Accounting Center Integration KIF Enables/Disables Network Access Designed for Easy Installation Meets and Network User Authentication Using LDAP or Active Directory Netgard
KIP Printer Status / SNMP	SNMP Communication to KIP Printer PC Based Windows® (LAN) Visual Notification for Machine Status View all KIP F	7/8 Application Monitor Status of KIP Printers Auto Detect KIP Printer

KIP 7770 SYSTEM INSTALLATION





pace, Electrical, and Environmental Requirements		
Weight	2 Roll: 734 lb. / 333 kg 4 Roll: 827 lb. / 375 kg	
Dimensions	67" (w) x 29" (d) x 59" (h) / 1702 mm (w) x 725 mm (d) x 1510 mm (h) with front delivery tray	
Electrical (Dedicated)	220 V - 240 V, 50/60 Hz, 16 amp	
Electrical Receptacle	Nema 6-20 R	
Max. Power Consumption	2.1 kWh (printing), 1.1 kWh (standby)	
Acoustic Noise	< 65 db (printing), <55 db (standby)	
Room Temperature	50-86°F (10-32°C)	
Room Humidity	15-85% (non condensing)	

Spatial Requirements (top view not to scale)





